

Technical Data Sheet



Ressi PlastoRend 120 C is a cement based ready to use premix plaster for internal and external use. Ressi PlastoRend 120 C can easily be applied with a suitable plastering machine or by hand in accordance to BS EN 13914-1 & BS EN 13914-2 **Ressi PlastoRend 120 C** provides a modern plastering system for fast application on walls and ceilings.

Advantages

- ✓ Ready to use; just add water
- ✓ Good machine flow
- ✓ Good adhesion to substrate
- ✓ Saves space (No dumping of sand on site)
- ✓ Accurate Cement content (No dosage errors)
- ✓ Consistent strength (No batch errors)
- ✓ Environmentally friendly; Less wastage
- ✓ Good compressive & flexural strength
- ✓ Durable color, UV stable pigments
- ✓ Save time (No site mix)
- ✓ Can be left bare or covered
- ✓ Good decorative finish

Surface preparation

All loose particles of dust and oil shall be cleaned off the surface prior to application. For very hot climatic conditions, the surface may be dampened with potable water. Over RCC and smooth concrete surfaces, it is recommended to coat **Ressi BRC 7000** before commencing the job for plastering.

Product preparation

For manual application it is important that water is premeasured in accordance with the amount of material used. The mortar powder should be added over the water to avoid the settlement of the material at the bottom of the mixing container. The mixing container should be uncontaminated, non corrosive and clean. Only potable water should be used for mixing. It is also recommended that material should be mechanically mixed with a mortar mixer or other mechanical mixing methods to obtain a consistent lump free mix.



RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com

Technical Data Sheet



Application

With proper surface preparation and mixing of the material, conventional plastering techniques can be used to apply **Ressi PlastoRend 120 C**. However, for speedy application it is strongly recommended to do proper surface preparation and spray the material using a plastering / rendering spray machine for higher output of work.

Technical Data

| | |
|--------------------------------------|--|
| Appearance | Colored Powder |
| Composition | Contains Cement, Construction grade pigments and selected aggregates along with additives to improve consistency, workability and durability |
| Maximum aggregates size | 2mm |
| * Water application | 22% \pm 5% |
| * Wet mix life | Tested as per BS EN 1015-9 Approximately < 2 hours @ 20°C |
| * Compressive Strength: ¹ | Tested as per BS EN 1015-11 28 Days 4.00 N/mm ² |
| * Flexural Strength | Tested as per BS EN 1015-12 28 Days 1.00N/mm ² |
| * Approximate Yield/Coverage | 0.66 m ³ /T |

* Typical results under laboratory conditions

¹ These results comply with BS EN 998-1 Class (CS III)



RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com

Technical Data Sheet



Curing

No curing required in general however, maximum curing for 72 hours where hot climatic conditions prevail.

Shelf life

Expiration of **Ressi PlastoRend 120 C** is at 6 months after production date under dry and sheltered conditions.

Health & Safety

Ressi PlastoRend 120 C is regarded as non hazardous for transportation. Do not reuse bags or containers and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application.

Packaging

Ressi PlastoRend 120 C is available in 50 KG and 20 KG bags.

Special note

For further color refernce, please refer to our shade card.



RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com