

Technical Data Sheet



Ressi ETA
Epoxy Tile Adhesive

Ressi ETA is a paste grade two component epoxy tile adhesive / glue. It forms a complete impermeable adhesive layer resistant to many forms of chemical attacks. **Ressi ETA** is useful for speedy fixing of tiles where high bond strength, impermeability to water and resistance to aggressive chemicals is essential. This tile adhesive is ideal for spaces such as battery rooms, transformer rooms, generator rooms, wet areas, kitchen, bathrooms, swimming pools etc.

Advantages

- ✓ Impermeable
- ✓ Non-Sag and easy to apply
- ✓ Early development of initial hardness, minimizes maintenance disruptions
- ✓ Pre-weighed quality controlled materials ensure consistency and reduce risk of site errors
- ✓ Unaffected by a wide range of acids, alkalis and industrial chemicals
- ✓ Excellent adhesion, suitable for a wide variety of tiles, granites, marbles etc.

Typical properties at 25°C

Component	Two: Part A: Base 3.4 Part Part B: Hardener 1 Part
Mixed Form	Paste
Color	Standard Color : Grey or transparent Other Colors available on request
*Mixed Density	1.8 Kg / Ltr \pm 0.05
*Open Time	>20 Mins (Tested as per BS EN 1346)
*Full Cure	7 Days
*Compressive Strength	75 N/mm ² @ 7 Days (Tested as per BS EN 6319-2)
*Tensile Strength	20 c @ 7 Days (Tested as per BS EN 6319-7)
*Initial shear adhesion	>2 N/mm ² @ 7 Days (Tested as per BS EN 12003)
*Flexural Strength	30 N/mm ² @ 7 Days (Tested as per BS EN 6319-3)
*Chemical Resistance	Resistance to various chemicals like mild acids, alkalis, grease, petrol, etc.

*Typical Results under laboratory conditions

These results comply with BS EN 12004 Type R Class 2 TE

RESSICHEM | ریسیکیم
adding life and value to your property | مضبوطی اور پائیداری کے لئے

RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com

Technical Data Sheet



Ressi ETA
Epoxy Tile Adhesive

Surface Preparation

All grease, oil, chemical, contamination, dust, laitance and loose particles must be removed by scrubbing or light brush hammering to provide a sound substrate. Concrete must be 14 days old prior to treatment. Steel surfaces should be grit blasted to white metal. Surfaces which show any trace of oil must be degreased with a chemical degreaser prior to grit blasting.

Mixing

Stir part A and part B separately to disperse any settlement. Mix part A with part B using a slow speed drill machine fitted with paddle until a uniform consistency is achieved.

Application

Apply the mixed **Ressi ETA** with a notched trowel to a thickness of 2mm on the prepared surface. Tiles should be placed within the working time of the adhesive.

Shelf Life

Expiration of **Ressi ETA** is at 06 months after production date under dry and sheltered conditions.

Packaging

Ressi ETA is available in 22 KG Sets

Part A 17 KG

Part B 5 KG

Coverage

5 SFT / Ltr @ 2mm Thickness

Health and Safety

Ressi ETA is regarded as non-hazardous for transportation. Do not reuse bags or containers and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application. Please refer to the MSDS of the product for further health and safety information.

RESSICHEM | ریسیکیم
adding life and value to your property | مضبوطی اور پائیداری کے لئے

RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com