

# Technical Data Sheet



## **Ressi TG 810** Colored tile grout

**Ressi TG 810** is a colorfast cementitious grouting for use as a joint filler for most types of ceramic tiles and natural stone applications. **Ressi TG 810** is waterproof and can be used for both internal and external application. **Ressi TG 810** is an ideal grout to be used for its application in bathrooms and swimming pools.

### Advantages

- ✓ Waterproof
- ✓ Prevents mold
- ✓ Good adhesion
- ✓ Does not stain tiles
- ✓ Excellent UV resistance
- ✓ Available in many colors
- ✓ Resistant to cracking
- ✓ No sealer required after application

### Surface Preparation

Before commencing grouting ensure that the tile adhesive has set firmly. The recommended tile adhesive to be used with **Ressi TG 810** is of the Ressi TA range. The usual requirement for the drying of the tile adhesive is 24 hours. Remove any spacer, lugs, scrape out any excess adhesive any loose foreign material from the grout joints. The joints have to be clean, free from dust deposits and other contaminations which may affect the adhesion. The suction in the background should be neutralizer by applying clean potable water. There should be no free water in the joints to be grouted as this could lead to de-bonding.

### Product Preparation

Pour premeasured clean water into a clean bucket and then slowly add the grout powder stirring continually until a lump free toothpaste consistency is achieved. The powder should be added over the water to avoid the settlement of the material at the bottom of the mixing container. The Mixing container should be uncontaminated, non-corrosive and clean. Only potable water should be used for mixing. It is also recommended that the material should be mechanically mixed with a mortar mixer or other mechanical mixing methods to obtain a consistent lump free mix.



**RESSICHEM (Pvt.) LIMITED**

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.  
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

[www.ressichem.com](http://www.ressichem.com)

# Technical Data Sheet



**Ressi TG 810**  
Colored tile grout

## Application

**Ressi TG 810** is to be applied with the tile joints using a rubber spatula, taking care to ensure that the grout is well compacted into the joints. The excess material on the surface of the tile should be removed using a dry cloth or sponge. Use a damp sponge to clean up the remainder of the grout. Regularly clean the sponge out to assist in cleaning.

## Technical Data

Appearance	Grey, White or Colored powder
Composition	Contains cement, & selected aggregates along with additives & pigments to improve consistency, workability & durability.
Maximum aggregate size	0.3mm
* Water application	36% ± 5%
* Wet Mix life	Tested as per BS EN 1015-9 approximately < 30 Minutes @ 20°C
* Approximate Yield / Coverage	0.85m <sup>3</sup> / T

\*Typical Results under laboratory conditions

## Curing

No Curing required

## Shelf Life

Expiration of **Ressi TG 810** at 12 months after production date under dry and sheltered conditions.

## Packaging

**Ressi TG 810** is available in 1 KG and 20 KG bags

## Health and Safety

**Ressi TG 810** is regarded as non-hazardous for transportation. Do not reuse bags or containers and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application. Please refer to the MSDS of the product for further health and safety information.

**RESSICHEM** | ریسیکیم  
adding life and value to your property | مضبوطی اور پائیداری کے لئے

**RESSICHEM (Pvt.) LIMITED**

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.  
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

[www.ressichem.com](http://www.ressichem.com)