

Technical Data Sheet



Ressi Tile Latex 205

Special Additive for Tile Adhesives to Enhance Bond Strength
Between Cemented Surfaces and Tile Base

Ressi Tile Latex 205 is an aqueous emulsion specially formulated for use as a bonding agent and as an additive with cementitious tile adhesives to improve the mix properties. It improves the waterproofing qualities, wear resistance, durability and bonding properties.

Advantages

- ✓ Improves the adhesion of tile adhesives to concrete, mortar and plaster
- ✓ Improves the flexural and tensile properties to allow for thin bed applications
- ✓ Improves cohesion and workability
- ✓ Reduces shrinkage
- ✓ Improves corrosion protection and durability
- ✓ Non-toxic

Technical properties at 25°C

Component	Single
Form	Liquid
Color	Milky White
*Specific Gravity	1.02 KG \pm 0.02
*Compressive Strength	10% – 15% increase over control
*Flexural Strength	5% - 10% increase over control
*Tensile Strength	5% - 10% increase over control

* Typical Results under laboratory conditions

Application

As a primer prior to adhering Tile adhesives to substrates use undiluted with a roller / brush and apply to the substrate that has to be tiled upon. Some very porous substrates may need 2 coats. All to be tacky (touch dry) before you apply the tile adhesive.

RESSICHEM | ریسیکیم
adding life and value to your property | مضبوطی اور پائیداری کے لئے

RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com

Technical Data Sheet



Ressi Tile Latex 205

Special Additive for Tile Adhesives to Enhance Bond Strength
Between Cemented Surfaces and Tile Base

Dosage

The dosage of this can vary from 1L to 20 KG tile adhesive to a complete water replacement.

Packaging

Available in 1 Ltr and 5 Ltr containers.

Shelf Life

12 months – unopened in dry weatherproof storage

Health and Safety

Ressi Tile Latex 205 is regarded as non-hazardous for transportation. Do not reuse bags or containers and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application. Please Refer to the MSDS of the product for further health and safety information.



RESSICHEM (Pvt.) LIMITED

Plot # D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi-75530, Pakistan.
Tel: +92 213 259 3800-02, Fax: +92 213 259 3803

www.ressichem.com