

**Zepoxy REH 115 X70** is a low viscosity solvent-based reactive polyamide curing agent for epoxy resin to be used in various applications.

## APPLICATIONS

- ✓ Tank and pipe coating
- ✓ Masonry and pool coatings
- ✓ Maintenance and marine coating
- ✓ High gloss coatings
- ✓ Adhesives and grouts

## ADVANTAGES

- ✓ Blended with other amine-based hardeners
- ✓ Excellent adhesion
- ✓ Good toughness and flexibility
- ✓ Good pigment and substrate wetting
- ✓ Long pot life

## TECHNICAL DATA

Property	Test Method	Result
Appearance	Visual	Clear, orange to brown liquid
*Color	ASTM D 1544	9 max.
*Amine value	ASTM D 1652	195 - 215 mg KOH/gm
*Viscosity @ 25°C	ASTM D 2196	1000 - 5000 cPs
*AHEW	-	271 AHEW
Mixing ratio with Zepoxy RER 011 X75	-	43 phr (Per hundred resin)

\*Typical results under laboratory conditions.

## PACKAGING

**Zepoxy REH 115 X70** is available in the following packaging:

1 KG, 5KG, 25KG, and 200KG

## HEALTH AND SAFETY

Dispose containers of the materials as per local laws, rules, and regulations. Use gloves, safety masks and other safety apparel as per health and safety laws. For further assistance, please refer to the MSDS of the product for further health and safety information.