

**Ressi Anchor Fix** is a three-component epoxy based high strength adhesive and anchor grout. It forms to give a strong, dense solid material. It is available in premeasured ready to use kit.

## STANDARDS

BS 6319: Part 2, BS 6319: PART 3, BS 6319: PART 7

## USES

**Ressi Anchor Fix** is used as epoxy grouting for bar anchor, starter bars, bridge bearing, boom fixing, bolts, nails, etc. It is used for speedy and permanent patching repairs to concrete structures, bonding of precast concrete components, bridge bearings to concrete and all structural repair works where strength, impermeability to water and resistance to aggressive chemicals is essential.

## ADVANTAGES

- ✓ High early strength
- ✓ Good adhesion to all substrates
- ✓ Unaffected by a wide range of acids, alkalis, and industrial chemicals
- ✓ 3 to 4 times stronger than typical concrete
- ✓ Excellent resistance to abrasion and impact.
- ✓ Vibration resistant
- ✓ Corrosion resistant
- ✓ Tolerant to damp conditions

## SURFACE PREPARATION

All surfaces should be dry, clean, free from standing water, grease, curing compounds, mold oils and all loosely adhering particles. Cement laitance should be removed by mechanical means. Roughen surfaces with chipping to ensure good bonding.

## MIXING

Mix component A and B together thoroughly with a slow speed drill for 1 minute (max 400 R.P.M.). Once the mixture is homogenous, Part C can be added as per the recommended ratio and packaging. The product is ready to use once all three components are mixed properly and homogenous.

## APPLICATION

**For Anchor Bolts:** Anchor bolt, dowel & starter bar holes must be dry. For bolts which will be placed into preformed holes, fill hole with **Ressi Anchor Fix** & gradually work the bolt into the grout.

**For Patching Work:** Apply the material by using notch trowel, scrapper or with a big spatula.

## QUANTITY ESTIMATE

Hole Diameter (mm)	Volume of Grout for bolt diameter					
	12	16	20	25	32	40
20	25					
25	50	40	25			
32	80	70	60	40		
38		130	100	75	45	
45			150	130	100	45
50				180	150	90
62					280	225

Volume of **Ressi Anchor Fix SG** in ml./100 mm. bond length

## SHELF LIFE

12 months from date of production, if stored properly in original unopened packing in dry conditions and away from sunlight and scorching heat.

## PACKAGING

**Ressi Anchor Fix** is available as follows.

3.8 KG Packs Part A: 1 KG  
 Part B: 800g  
 Part C: 2 KG

38 KG Packs Part A: 10 KG  
 Part B: 08 KG  
 Part C: 20 KG



PRINTED



UNIVERSAL

**NOTE:**

If printed packaging not available, neutral packaging with label. Lot number and manufacturing date to be stamped at the back of each packaging.

TECHNICAL DATASHEET RESSI ANCHOR FIX