



Crack Heal Flexi 950 is a single component ready to use acrylic based crack and joint filler, **Crack Heal Flexi 950** is suitable for filling cracks, joints, and voids on most types of absorbent surfaces such as plaster, wood gypsum, asbestos etc. **Crack Heal Flexi 950** is suitable for fixing crack up to 4mm wide.

ADVANTAGES

- ✓ Crack filling ability – Strong filling capacity for cracks up to 4mm width in a single layer.
- ✓ Flexibility – High elongation film that accommodates movement.
- ✓ Waterproofing - Water Resistant film stops water Ingress through cracks.
- ✓ Adhesion – Very strong adhesion, on absorbent surfaces.
- ✓ Usage – Single Pack ready to use and easy to apply product.
- ✓ Over Coating – Easily over coated by any emulsion paint.

TECHNICAL DATA

Form	Ready to use paste
Density at 25°C	1.28
Drying Time	Minimum 6 hours depending on temperature and humidity
Flash Point	Crack Heal is water based which is nonflammable
Consumption	75 – 80 running feet / KG / 2 coats @ 3mm Wide and 5mm depth.

*Typical results under laboratory conditions

SURFACE PREPARATION

It is recommended to open the hairline cracks wide to form a “V” shaped groove. This will provide a strong base for the adhesion of **Crack Heal 950**. It is recommended to use a cutter for opening the cracks. All loose particles for dust and oil shall be cleaned off the surface prior to application. For hot climatic conditions, the surface can be dampened with potable water.

PRODUCT PREPARATION

The product is ready to use. No modifications to the product is recommended. In case the product becomes too viscous some water can be added to the product to adjust the viscosity as desired.

APPLICATION

Crack Heal Flexi 950 can be applied using a putty knife / trowel. It can also be levelled using **Paint Guard 10,000 C** after which it can be painted overusing a suitable paint.

CURING

No curing required.



SHELF LIFE

Expiration of **Crack Heal 950** is 6 months after production date under dry and sheltered conditions.

PACKAGING

Crack Heal Flexi 950 is available in 2 KG pouches and 20 KG Buckets.

HEALTH AND SAFETY

Crack Heal 950 is not regarded hazardous for transportation. Do not reuse the packaging and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application. Please refer to the MSDS of the product for further health and safety information.