

### MATERIAL SAFETY DATA SHEET

Updated on: 04-Feb-2024

### 1. Identification

Product Identifier:	ZEPOXY TABLE TOP DEEP POUR
Synonyms:	BPA based epoxy resin & Amine based curing agent
Manufacturer of	Ressichem Pvt. Ltd.
Zepoxy Table Top Deep Pour :	D-83, S.I.T.E Industrial area, Mangophir Road, Karachi.
Email:	<u>info@ressichem.com</u>
	www.ressichem.com
Emergency Phone Number:	+92 2132593800
	+92 309 7772464

### 2. Composition/Information on Ingredients

### Part A

Chemical Name:	Diglycidyl ether of bisphenol-A
Chemical Formula:	Variable, typically (CH2-CH2-O-R-O-CH2-CH2)n
Part B	
Chemical Name:	Polyetheramine
Chemical Formula:	$Variable, typically C_2H_5C[CH_2[OCH_2CH(CH_3)]_nNH_2]_3$

### 3. Hazards Identification

### **Classification of the Substance or Mixture:**

GHS Classification:	
Hazards:	

May cause skin irritation. May cause eye irritation. Harmful if swallowed. May cause respiratory irritation.

### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Wear protective gloves/eye protection/face protection.

### Response:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. Remove person to fresh air and keep comfortable for breathing.

Not classified as hazardous according to GHS criteria.

# If inhaled:

## Storage:

Store locked up. Store in a well-ventilated place.

### Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.





4. Fire-Fighting M	Measures			
Special Firefighting Procedu	esistant foam, dry chemical, or carbon dioxide.			
5. First Aid Measu	ures			
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.			
Skin Contact:	Wash affected area thoroughly with soap and water.			
Eye Contact:	Flush eyes with plenty of water for at least 15 minutes. Ensure adequate flushing by separating eyelids with fingers.			
Ingestion:	Rinse mouth with water. Do not induce vomiting. Seek medical attention immediately.			
6. Accidental Rele	ease Measures			
Personal Precautions:	Wear appropriate protective equipment.			
Environmental Precautions:				
Methods for Containment ar	nd Clean-Up: Absorb spillage with non-combustible absorbent material. Scoop up with a non-sparking tool.			
7. Handling and S	jtorage			
Handling:				
Storage:	Store in a cool, dry, well-ventilated area away from incompatible materials.			
5	Keep containers tightly closed when not in use.			
8. Exposure Cont	trols/Personal Protection			
Engineering Controls:	Use local exhaust ventilation to maintain airborne concentrations below exposure limits.			
Personal Protective	•			
Eye Protection:	Safety glasses or goggles.			
Skin Protection:	Wear protective gloves and clothing.			
Respiratory Protection:	Use NIOSH approved respirator if ventilation is inadequate.			
	ose moon approved respirator in ventilation is inadequate.			
	chemical Properties			
9. Physical and Cl Part A	hemical Properties			
9. Physical and C				
9. Physical and Cl Part A Appearance: Odor:	Chemical Properties Low Viscous, Clear, Liquid Characteristic			
9. Physical and Cl Part A Appearance: Odor: pH:	chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable			
9. Physical and Cl Part A Appearance: Odor:	Chemical Properties Low Viscous, Clear, Liquid Characteristic			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F)			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate:	Ehemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1)			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscous, Clear, Liquid			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor:	Low Viscous, Clear, Liquid         Characteristic         Not applicable         205 - 248 °C (401 - 478 °F)         Variable         Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828         Less than 1 (n-Butyl acetate=1)         Not flammable         Insoluble in water         Low Viscous, Clear, Liquid         Characteristic			
9. Physical and Cl Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor: pH:	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscous, Clear, Liquid Characteristic Not applicable			
<ul> <li>9. Physical and Cl</li> <li>Part A</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> <li>Melting Point/Range:</li> <li>Flash Point:</li> <li>Evaporation Rate:</li> <li>Flammability:</li> <li>Solubility:</li> <li>Part B</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> </ul>	Low Viscous, Clear, Liquid         Characteristic         Not applicable         205 - 248 °C (401 - 478 °F)         Variable         Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828         Less than 1 (n-Butyl acetate=1)         Not flammable         Insoluble in water         Low Viscous, Clear, Liquid         Characteristic         Not applicable         205 - 248 °C (401 - 478 °F)			
<ul> <li>9. Physical and Cl Part A</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> <li>Melting Point/Range:</li> <li>Flash Point:</li> <li>Evaporation Rate:</li> <li>Flammability:</li> <li>Solubility:</li> <li>Part B</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> <li>Melting Point/Range:</li> <li>Melting Point/Range:</li> <li>Melting Point/Range:</li> </ul>	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable			
<ul> <li>9. Physical and Cl</li> <li>Part A</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> <li>Melting Point/Range:</li> <li>Flash Point:</li> <li>Evaporation Rate:</li> <li>Flammability:</li> <li>Solubility:</li> <li>Part B</li> <li>Appearance:</li> <li>Odor:</li> <li>pH:</li> <li>Boiling Point/Range:</li> <li>Melting Point/Range:</li> <li>Melting Point/Range:</li> <li>Flash Point:</li> </ul>	Chemical Properties Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscous, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828			



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02
 +92-309-7772464



10. Stability and Read	tivity				
Chemical Stability: Stab	le under norma	l conditions.			
Possibility of Hazardous Reaction	ons:	None under normal conditions.			
Conditions to Avoid:		Heat, flames, sparks, and other sources of ignition.			
Incompatible Materials:		Strong oxidizing agents, acids, bases.			
Hazardous Decomposition Produ	ucts:	Carbon monoxide, ca	Carbon monoxide, carbon dioxide, nitrogen oxides.		
11. Toxicological Info	rmation				
Acute Toxicity:		LD50 (Oral, Rat): > 2,0	LD50 (Oral, Rat): > 2,000 mg/kg (estimated)		
Skin Irritation:		May cause skin irrita	May cause skin irritation.		
Eye Irritation:		May cause eye irrita	May cause eye irritation.		
Sensitization:		Not a skin sensitizer	Not a skin sensitizer.		
Carcinogenicity:		Not classified as carcinogenic.			
12. Ecological Inform	ation				
Ecotoxicity:		No data available.	√o data available.		
Persistence and Degradability:	No data availab				
Bioaccumulative Potential:		No data available.			
<b>13. Disposal Conside</b> Dispose of waste material in ac		al, regional, national, and interna	tional regulations.		
	on is for information o	nly and may not be specific to yo y your shipment for transportatio	ur package size ormode of transport. You will need to n.		
Regulatory information	UN number	Proper shipping name	Classes/Packing Group		
CFR	number 3082 / 2735	RESIN / HARDENER	Class 8 III		
TNG	3082 / 2735	RESIN / HARDENER	Class 8 III		

# TDG3082 / 2735RESIN / HARDENERClass 8 IIIIMO/IMDG3082 / 2735RESIN / HARDENERClass 8 IIIIATA (Cargo)3082 / 2735RESIN / HARDENERClass 8 IIIMarine Polluted :YESYESYES

### 15. Regulatory Information

There are no established exposure limits for the mixture, however, dust and fumes from processing should be ventilated adequately. To the best of our knowledge:

None of the mixture components are on the health & safety reporting list.

None of the mixture components are in this product are under a Chemical Test Rule.

None of the mixture components are listed under TSCA section 12b (export notification).

None of the mixture components in this material have an SNUR under TSCA.

None of the mixture components in this material have an RQ under CERLCA.

None of the mixture components in this material have a TPQ under SARA.

None of the mixture components in this material is reported under section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

Clean Water Act: None of the chemicals in this product are listed as hazardous substances under the CWA.

None of the chemicals in this product are listed as priority pollutants under CWA.

None of the chemicals in this product are listed as toxic pollutants under CWA.

OSHA:



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02
 +92-309-7772464

www.ressichem.com



None of the chemicals in this product are considered highly hazardous by OSHACalifornia Prop 65:California no significant risk level: none of the chemicals in this product are listed. European / International RegulationsEuropean labeling in accordance with EU/EC Directives.Hazard Symbols:not availableRisk Phrases:no Information availableSafety Phrases:no Information availableWGK:no Information available.

### 16. Other Information

This Material Safety Data Sheet (MSDS) is provided for informational purposes only. The information contained herein is believed to be accurate, but no representations, guarantees, or warranties of any kind are made to its accuracy, reliability, or completeness.



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02 +92-309-7772464
 www.ressichem.com