

MATERIAL SAFETY DATA SHEET

Updated on: 04-Feb-2024

1. Identification

Product Identifier:	ZEPOXY 100
Synonyms:	BPA based epoxy resin & Amine based curing agent
Manufacturer of	Ressichem Pvt. Ltd.
Zepoxy 100 :	D-83, S.I.T.E Industrial area, Mangophir Road, Karachi.
Email:	<u>info@ressichem.com</u>
	www.ressichem.com
Emergency Phone Number:	+92 2132593800
	+92 309 7772464

2. Composition/Information on Ingredients

Part A

Chemical Name:	Diglycidyl ether of bisphenol-A
Chemical Formula:	Variable, typically (CH2-CH2-O-R-O-CH2-CH ₂) _n
Part B	
Chemical Name:	Aliphatic Polyamide
Chemical Formula:	Variable, typically CnH(2n+1)NH2

3. Hazards Identification

Classification of the Substance or Mixture:

GHS Classification:	Not classified as hazardous according to GHS criteria.
Hazards:	
May cause skin irritation.	
May cause eye irritation.	
Harmful if swallowed.	
May cause respiratory irritation	
Prevention:	

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Response:

lf in eyes:	Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue		
	rinsing.		
If swallowed:	Rinse mouth. Do NOT induce vomiting.		
lf on skin:	Wash with plenty of water.		
If inhaled:	Remove person to fresh air and keep comfortable for breathing.		
_			

Storage:

Store locked up.

Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.





e. vent contact with skin and eyes. ve artificial respiration. If breathing is difficult, give oxygen. ap and water. east 15 minutes. Ensure adequate flushing by separating eyelids with vomiting. Seek medical attention immediately. ive equipment. to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials. ot in use.		
ive artificial respiration. If breathing is difficult, give oxygen. ap and water. east 15 minutes. Ensure adequate flushing by separating eyelids with vomiting. Seek medical attention immediately. ive equipment. to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials.		
ap and water. east 15 minutes. Ensure adequate flushing by separating eyelids with vomiting. Seek medical attention immediately. ive equipment. to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials.		
ive equipment. to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials.		
to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. -hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials.		
to soil, waterways, or drains. -combustible absorbent material. Scoop up with a non-sparking tool. -hing. Use with adequate ventilation .Wash thoroughly after handling. ea away from incompatible materials.		
ea away from incompatible materials.		
ea away from incompatible materials.		
Sure Controls/Personal Protection Controls: Use local exhaust ventilation to maintain airborne concentrations below exposure limits. Protective Equipment: Safety glasses or goggles. ion: Safety gloves and clothing. Protection: Use NIOSH approved respirator if ventilation is inadequate.		
colorless to light yellow Liquid cteristic plicable 248 °C (401 - 478 °F) le er than 126 °C (258.8 °F) Seta flash Closed Cup ASTM D 3828 han 1 (n-Butyl acetate=1) immable ble in water Orange to brown Liquid cteristic plicable 248 °C (401 - 478 °F) le		
ib te tl la ul r, aip - 2		



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
+92-21-32593800-02
+92-309-7772464

left www.ressichem.com



10. Stability and Reactivity

Chemical Stability: Stable under normal conditions

Chemical Stability: Stable under normal conditions.				
Possibility of Hazardous Reactions:	lous Reactions: None under normal conditions.			
Conditions to Avoid:	Heat, flames, sparks, and other sources of ignition.			
Incompatible Materials:	Strong oxidizing agents, acids, bases.			
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, nitrogen oxides.			
11. Toxicological Information				
Acute Toxicity:	LD50 (Oral, Rat): > 2,000 mg/kg (estimated)			
Skin Irritation:	May cause skin irritation.			
Eye Irritation:	May cause eye irritation.			
Sensitization:	Not a skin sensitizer.			
Carcinogenicity:	Not classified as carcinogenic.			
12. Ecological Information				
Ecotoxicity:	No data available.			
Persistence and Degradability:	No data available.			
Bioaccumulative Potential:	No data available.			
13 Disposal Considerations				

13. Disposal Considerations

Dispose of waste material in accordance with all local, regional, national, and international regulations.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size ormode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Regulatory information	n UN number	Proper shipping name	Classes/Packing Group
CFR	3082 / 2735	RESIN / HARDENER	Class 8 III
TDG	3082 / 2735	RESIN / HARDENER	Class 8 III
IMO/IMDG	3082 / 2735	RESIN / HARDENER	Class 8 III
IATA (Cargo)	3082 / 2735	RESIN / HARDENER	Class 8 III
Marine Polluted :	YES		

15. Regulatory Information

There are no established exposure limits for the mixture, however, dust and fumes from processing should be ventilated adequately. To the best of our knowledge:

None of the mixture components are on the health & safety reporting list.

None of the mixture components are in this product are under a Chemical Test Rule.

None of the mixture components are listed under TSCA section 12b (export notification).

None of the mixture components in this material have an SNUR under TSCA.

None of the mixture components in this material have an RQ under CERLCA.

None of the mixture components in this material have a TPQ under SARA.

None of the mixture components in this material is reported under section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

Clean Water Act: None of the chemicals in this product are listed as hazardous substances under the CWA.

None of the chemicals in this product are listed as priority pollutants under CWA.

None of the chemicals in this product are listed as toxic pollutants under CWA.

OSHA:



www.ressichem.com



None of the chemicals in this product are considered highly hazardous by OSHACalifornia Prop 65:California no significant risk level: none of the chemicals in this product are listed. European / International RegulationsEuropean labeling in accordance with EU/EC Directives.Hazard Symbols:not availableRisk Phrases:no Information availableSafety Phrases:no Information availableWGK:no Information available.

16. Other Information

This Material Safety Data Sheet (MSDS) is provided for informational purposes only. The information contained herein is believed to be accurate, but no representations, guarantees, or warranties of any kind are made to its accuracy, reliability, or completeness.



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
+92-21-32593800-02 +92-309-7772464
www.ressichem.com