



**Ressi Acid Itch** is a product composed of strong acid buffered by surfactants and anti-foaming. It attacks surfaces with the strength of the acid and removes dirt and grease with the power of a detergent. Applied to concrete, it is designed to open pores of the surface to allow any further processing of painting and floor protection. Its application on tile and clinker is designed to remove dirt and any concentration of lime. It can be used as a cleaner to prepare concrete surfaces that will be treated with Ressi Reactive Stains and appropriate sealers from the Ressichem range.

### APPLICATION

**Ressi Acid Itch** can be diluted in water, dilution ratio of 1:5 (1 part of **Ressi Acid Itch** with 5 parts of Water). Apply with a floor machine or flooring buffer. Always check that there is no bare metal. Rinse thoroughly with clean water.

#### COVERAGE

100g/m<sup>2</sup> of diluted product 20g/m<sup>2</sup> of pure product

### PACKAGING

Ressi Acid Itch is available in 1Ltr, 5Ltr, 10 Ltr, 15 Ltr, and 25 Ltr Packs.

# SHELF LIFE

The original packaging when stored at 10°C to 30°C will last for 12 months. Excess environmental moisture will reduce shelf life.

# **HEALTH & SAFETY**

**Ressi Acid Itch** is a corrosive product, protect eyes, face, and skim from coming in direct contact with the material. It is sensitive to cold temperatures. The material is for professional use only. Special care should be taken while transporting the material. Appropriate gloves and safety equipment should be worn. Do not reuse bags or containers and dispose them off as per local rules and regulations.



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
+92-21-32593800-02 +92-309-7772464
www.ressichem.com

PAGE: 1 OF 1