

Ressi DecoRend 20,000 C is cement based water resistant decorative thin applied plaster which is ideal for use on concrete / Plastered walls and ceilings. It fills fine pores of plaster and concrete and provides a smooth and dry surface. **Ressi DecoRend 20,000 C** is an ideal Fine Plaster to be used in combination with **Ressi PlastoRend 120, Insulaster, Conventional Plaster of good quality** or any other base plaster material by Ressichem Prior to finishing it. **Ressi DecoRend 20,000 C** is suitable for many mineral based backgrounds and plasters Further paints and Wallpapers can be applied over **Ressi DecoRend 20,000 C** if needed.

ADVANTAGES

- ✓ Better adhesion and durability compared to other acrylic based finishing materials.
- ✓ Applicable on both internal and external surface.
- ✓ No curing required.
- ✓ Water resistant, application on moist surfaces possible (2 Coat application).
- ✓ Smooth Finish.
- ✓ Any type of paint or distemper can be applied on Ressi DecoRend 20,000 C
- ✓ No primer required prior to application.
- ✓ Helps in preventing the growth of algae and fungus on walls.
- ✓ Premixed material; just add water.

SURFACE PREPARATION

Remove all loose particles, dust, oil, grease, and any other material which may result in poor adhesion from the substrate. The surface required for the application of **Ressi DecoRend 20,000 C** is usually a concrete levelled surface or a levelled plastered surface. It is essential to have a levelled base plaster surface prior to the application of **Ressi DecoRend 20,000 C** to avoid level waves in the finished product if a smooth and levelled surface is required.

PRODUCT PREPARATION

It is important that water is premeasured in accordance with the amount of material used. **Ressi DecoRend 20,000 C** should be added over the water to avoid the settlement of the material at the bottom of the mixing container. The mixing container should be uncontaminated, non-corrosive and clean. Only potable water should be used for mixing. If certain shades of the material are required which are not standardized by Ressichem, certain oxides and pigments can be added by the applicator on site to make a shade, however consistent dosage and water proportions are essential to maintain stable colors of the products. Ressichem Does not take any responsibility for color variations which may occur based on the addition of external pigments in its materials.

APPLICATION

Ressi DecoRend 20,000 C is applied onto the prepared surface using a painter's knife, Steel trowel or appropriate tools used to achieve the desired thickness of 1mm and above and finish of the product. **Ressi DecoRend 20,000 C** is not a brush applied material. It is recommended to build up the thickness of this material layer by layer. The total thickness of one coat should be limited to no more than 2mm. Multiple coats can be applied.

TECHNICAL DATA

Appearance	Grey, White or Colored Powder
Composition	Contains cement and selected aggregates along with additives to improve consistency, workability, and durability
*Maximum Aggregate Size	0.3 mm
*Water application	40% ± 5%
*Wet Mix Life	Approximately 30 Mins @ 20°C (Tested as per BS EN 1015-9)
*Compressive Strength	10.00 N / mm ² @ 28 Days (Tested as per BS EN 1015-11)
*Flexural Strength	3.00 N / mm ² @ 28 Days (tested as per BS EN 1015-12)
*Approximate Yield / Coverage	0.85 m ³ / T

*Typical Results under laboratory conditions.

CURING

No curing required in general, however if temperature during application exceed 40°C, curing for 48 Hours is recommended.

SHELF LIFE

Expiration of **Ressi DecoRend 20,000 C** is 6 months after production date under dry and sheltered conditions.

PACKAGING

Ressi DecoRend 20,000 C is available in 1 KG and 12 KG Packs



PRINTED BAG



UNIVERSAL BAG

NOTE:

If printed bags are not available, neutral bags with label. Lot number and manufacturing date to be stamped at the back of each bag.

HEALTH AND SAFETY

Ressi DecoRend 20,000 C is regarded as non-hazardous for transportation. Do not reuse bags or containers and dispose of them as per local rules and regulations. Gloves and suitable masks can be worn during application. Please refer to the MSDS of the product for further health and safety information.

SPECIAL NOTE

Ressi DecoRend 20,000 C is available in 6 Standard Shades including White. It is Recommended to have shade verifications prior to the purchase of Materials.