



Ressi Grout latex 805 is an aqueous emulsion specially formulated for use as a bonding agent and as an additive with cementitious tile grouts to improve the mix properties. It improves the waterproofing qualities, wear resistance, durability, and bonding properties.

ADVANTAGES

- Improved adhesion to both old and new surfaces.
- → Helps in the reduction of dusting and cracking of tile grout joints.
- ✓ Improved resilience for thermal movement.
- Improved chemical resistance of grout joints.
- ✓ Improved resistance to water infiltration.

TECHNICAL PROPERTIES AT 25°C

Component	Single
Form	Liquid
Color	Milky White
*Specific Gravity	1.02 KG ± 0.02
*Compressive Strength	10% – 15% increase over control
*Flexural Strength	5% - 10% increase over control
Tensile Strength	5% - 10% increase over control

^{*}Typical results under laboratory conditions

APPLICATION

As a primer: prior to adhering Tile grouts to substrates use undiluted brush and apply to the substrate that has to be grouted upon. Some very porous substrates may need 2 coats. All to be tacky (touch dry) before you apply the tile adhesive.

As an additive: The dosage of this can vary from 1L to 20 KG tile grout to a complete water replacement.

PACKAGING

Ressi Grout Latex 805 is available as follows:

1Ltr, 5Ltr, 15Ltr, 25Ltr and 200Ltr



O-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan

www.ressichem.com









NOTE:

If printed stickers are not available, neutral stickers with label. Lot number and manufacturing date to be stamped at the sticker.

SHELF LIFE

12 months - unopened in dry weatherproof storage

HEALTH AND SAFETY

Ressi Grout Latex 805 is regarded as non-hazardous for transportation. Do not reuse bags or containers and dispose them off as per local rules and regulations. Gloves and suitable masks can be worn during application. Please refer to the MSDS of the product for further health and safety information.

