

**Zepoxy Accl 5130** is a low viscosity accelerator for epoxy resins. It shows good chemical resistance and is compatible with a wide range of solvents.

## APPLICATIONS

It is an activator for other curing agents including amidoamines, amine adducts and polyamides (coatings, castings, flooring, concrete and adhesives applications). It is also the preferred catalyst for blends of liquid epoxy resin and liquid polysulfide for body solder, sealant, and concrete adhesives applications. Also, it is a highly efficient catalyst for epoxy resins cured with poly-carboxylic acids and anhydrides (casting and laminate applications)

## TECHNICAL DATA

Property	Test Method	Result
Appearance	Visual	Amber color liquid
*Color	ASTM D 1544-04	7 G max.
*Viscosity @ 25°C	ASTM D 3236-09	150 – 250 cPs
*Density @ 25°C	ASTM D 1475-98	0.98 g/cc
Recommended phr level	-	1-5

\*Typical results under laboratory conditions

## PACKAGING

**Zepoxy Accl 5130** is available as follows:

1 KG, 5KG, 15KG, 30KG, and 200KG

## HEALTH AND SAFETY

Dispose containers of the materials as per local laws, rules, and regulations. Use gloves, safety masks and other safety apparel as per health and safety laws. For further assistance, please refer to the MSDS of the product for further health and safety information.