

#### MATERIAL SAFETY DATA SHEET

Updated on: 28-May-2024

#### 1. Identification

Product Identifier: ZEPOXY ELECTRO FLEX

Synonyms: Clear Electronic Component Potting Adhesive

Manufacturer of Ressichem Pvt. Ltd.

Zepoxy Electro Flex: D-83, S.I.T.E Industrial area, Mangophir Road, Karachi.

Email: <a href="mailto:info@ressichem.com">info@ressichem.com</a>

www.ressichem.com

Emergency Phone Number: +92 2132593800

+92 309 7772464

## 2. Composition/Information on Ingredients

Part A

Chemical Name: Diglycidyl ether of bisphenol-A

Chemical Formula: Variable, typically (CH2-CH2-O-R-O-CH2-CH<sub>2</sub>)<sub>n</sub>

Part B

Chemical Name: Cycloaliphatic Polyamide
Chemical Formula: Variable, typically CnH(2n+1)N

#### 3. Hazards Identification

#### Classification of the Substance or Mixture:

GHS Classification: Not classified as hazardous according to GHS criteria.

Hazards:

May cause skin irritation. May cause eye irritation. Harmful if swallowed.

May cause respiratory irritation.

#### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Response:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue

rinsing.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

**Storage:** Store locked up.

Store in a well-ventilated place.

#### Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.



O-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan

**t** +92-21-32593800-02 📮 +92-309-7772464



# 4. Fire-Fighting Measures

## **Extinguishing Media:**

Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

Special Firefighting Procedures:

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

#### 5. First Aid Measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Skin Contact: Wash affected area thoroughly with soap and water.

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Ensure adequate flushing by separating eyelids with

finaers.

Ingestion: Rinse mouth with water. Do not induce vomiting. Seek medical attention immediately.

### 6. Accidental Release Measures

Personal Precautions: Wear appropriate protective equipment.

Environmental Precautions: Prevent from entering into soil, waterways, or drains.

Methods for Containment and Clean-Up: Absorb spillage with non-combustible absorbent material. Scoop up with a non-sparking tool.

## 7. Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Use with adequate ventilation .Wash thoroughly after handling.

Storage: Store in a cool, dry, well-ventilated area away from incompatible materials.

Keep containers tightly closed when not in use.

### 8. Exposure Controls/Personal Protection

Engineering Controls: Use local exhaust ventilation to maintain airborne concentrations below exposure limits.

### **Personal Protective Equipment:**

Eye Protection: Safety glasses or goggles.

Skin Protection: Wear protective gloves and clothing.

Respiratory Protection: Use NIOSH approved respirator if ventilation is inadequate.

## 9. Physical and Chemical Properties

#### Part A

Appearance: Clear Liquid
Odor: Characteristic
pH: Not applicable

Boiling Point/Range: 205 - 248 °C (401 - 478 °F)

Melting Point/Range: Variable

Flash Point: Greater than 150 °C (302 °F) Seta flash Closed Cup ASTM D 3828

Evaporation Rate: Less than 1 (n-Butyl acetate=1)

Flammability: Not flammable Solubility: Insoluble in water

Part B

Appearance: Clear Liquid
Odor: Characteristic
pH: Not applicable

Boiling Point/Range: 205 - 248 °C (401 - 478 °F)

Melting Point/Range: Variable

Flash Point: Greater than 93.4°C (200.1°F) Seta flash Closed Cup ASTM D 3828

Evaporation Rate: Less than 1 (n-Butyl acetate=1)

Flammability: Not flammable Solubility: Insoluble in water





### 10. Stability and Reactivity

### Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: None under normal conditions.

Conditions to Avoid: Heat, flames, sparks, and other sources of ignition.

Incompatible Materials: Strong oxidizing agents, acids, bases.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides.

# 11. Toxicological Information

Acute Toxicity: LD50 (Oral, Rat): > 2,000 mg/kg (estimated)

Skin Irritation:May cause skin irritation.Eye Irritation:May cause eye irritation.Sensitization:Not a skin sensitizer.Carcinogenicity:Not classified as carcinogenic.

### 12. Ecological Information

Ecotoxicity: No data available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

### 13. Disposal Considerations

Dispose of waste material in accordance with all local, regional, national, and international regulations.

### 14. Transport Information

The data provided in this section is for information only and may not be specific to your package size ormode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Regulatory information	UN number	Proper shipping name	Classes/Packing Group
CFR	3082 / 2735	RESIN / HARDENER	Class 8 III
TDG	3082 / 2735	RESIN / HARDENER	Class 8 III
IMO/IMDG	3082 / 2735	RESIN / HARDENER	Class 8 III
IATA (Cargo)	3082 / 2735	RESIN / HARDENER	Class 8 III

Marine Polluted : YES

### 15. Regulatory Information

There are no established exposure limits for the mixture, however, dust and fumes from processing should be ventilated adequately. To the best of our knowledge:

None of the mixture components are on the health & safety reporting list.

None of the mixture components are in this product are under a Chemical Test Rule.

None of the mixture components are listed under TSCA section 12b (export notification).

None of the mixture components in this material have an SNUR under TSCA.

None of the mixture components in this material have an RQ under CERLCA.

None of the mixture components in this material have a TPQ under SARA.

None of the mixture components in this material is reported under section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

Clean Water Act: None of the chemicals in this product are listed as hazardous substances under the CWA.

None of the chemicals in this product are listed as priority pollutants under CWA.

None of the chemicals in this product are listed as toxic pollutants under CWA.

OSHA:



www.ressichem.com



None of the chemicals in this product are considered highly hazardous by OSHA

California Prop 65:

California no significant risk level: none of the chemicals in this product are listed. European / International Regulations

European labeling in accordance with EU/EC Directives. Hazard Symbols: not available

Risk Phrases: no Information available
Safety Phrases: no Information available
WGK: no Information available.

### 16. Other Information

This Material Safety Data Sheet (MSDS) is provided for informational purposes only. The information contained herein is believed to be accurate, but no representations, guarantees, or warranties of any kind are made to its accuracy, reliability, or completeness.

