

MATERIAL SAFETY DATA SHEET

Updated on: 6-May-2024

1. Identification

Product Identifier:	ZEPOXY GLASS CAST PLUS
Synonyms:	BPA based epoxy resin & Amine based curing agent
Manufacturer of	Ressichem Pvt. Ltd.
Zepoxy Glass Cast Plus :	D-83, S.I.T.E Industrial area, Mangophir Road, Karachi.
Email:	<u>info@ressichem.com</u>
	www.ressichem.com
Emergency Phone Number:	+92 2132593800
	+92 309 7772464

2. Composition/Information on Ingredients

Part A

Chemical Name:	Diglycidyl ether of bisphenol-A
Chemical Formula:	Variable, typically (CH2-CH2-O-R-O-CH2-CH2)n
Part B	
Chemical Name:	Polyetheramine
Chemical Formula:	Variable, typically $C_2H_5C[CH_2[OCH_2CH(CH_3)]_nNH_2]_3$

3. Hazards Identification

Classification of the Substance or Mixture:

GHS Classification:	
II	

Hazards: May cause skin irritation. May cause eye irritation. Harmful if swallowed. May cause respiratory irritation.

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Response:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. Remove person to fresh air and keep comfortable for breathing.

Not classified as hazardous according to GHS criteria.

If inhaled:

Storage:

Store locked up. Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.





4. Fire-Fighting M	leasures		
Special Firefighting Procedu	sistant foam, dry chemical, or carbon dioxide.		
5. First Aid Measu	ures		
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.		
Skin Contact:	Wash affected area thoroughly with soap and water.		
Eye Contact:	Flush eyes with plenty of water for at least 15 minutes. Ensure adequate flushing by separating eyelids with fingers.		
Ingestion:	Rinse mouth with water. Do not induce vomiting. Seek medical attention immediately.		
6. Accidental Rele	ease Measures		
Personal Precautions:	Wear appropriate protective equipment.		
Environmental Precautions:			
Methods for Containment ar	nd Clean-Up: Absorb spillage with non-combustible absorbent material. Scoop up with a non-sparking tool.		
7. Handling and S	torage		
Handling:	Avoid contact with eyes, skin, and clothing. Use with adequate ventilation .Wash thoroughly after handling.		
Storage:	Store in a cool, dry, well-ventilated area away from incompatible materials.		
·	Keep containers tightly closed when not in use.		
8. Exposure Cont	rols/Personal Protection		
Engineering Controls:	Use local exhaust ventilation to maintain airborne concentrations below exposure limits.		
Personal Protective	•		
Eye Protection:	Safety glasses or goggles.		
Skin Protection:	Wear protective gloves and clothing.		
Respiratory Protection:	Use NIOSH approved respirator if ventilation is inadequate.		
9. Physical and C	hemical Properties		
9. Physical and Cl Part A	hemical Properties		
Part A			
•	hemical Properties Low Viscosity, Clear, Liquid Characteristic		
Part A Appearance: Odor:	- Low Viscosity, Clear, Liquid Characteristic		
Part A Appearance: Odor: pH:	- Low Viscosity, Clear, Liquid Characteristic Not applicable		
Part A Appearance: Odor:	- Low Viscosity, Clear, Liquid Characteristic		
Part A Appearance: Odor: pH: Boiling Point/Range:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F)		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1)		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid Characteristic		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor: pH:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid Characteristic Not applicable		
Part A Appearance: Odor: pH: Boiling Point/Range: Metting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor: pH: Boiling Point/Range:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F)		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable		
Part A Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point: Evaporation Rate: Flammability: Solubility: Part B Appearance: Odor: pH: Boiling Point/Range: Melting Point/Range: Flash Point:	Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828 Less than 1 (n-Butyl acetate=1) Not flammable Insoluble in water Low Viscosity, Clear, Liquid Characteristic Not applicable 205 - 248 °C (401 - 478 °F) Variable Greater than 150°C (302 °F) Seta flash Closed Cup ASTM D 3828		



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02
 +92-309-7772464



Chemical Stability: Stab					
Possibility of Hazardous Reactions:			None under normal conditions.		
Conditions to Avoid:			Heat, flames, sparks, and other sources of ignition.		
Incompatible Materials:			Strong oxidizing agents, acids, bases.		
Hazardous Decomposition Produ	JCts:	Carbon monoxide, ca	Carbon monoxide, carbon dioxide, nitrogen oxides.		
11. Toxicological Info	rmation				
Acute Toxicity:		LD50 (Oral, Rat): > 2,0	LD50 (Oral, Rat): > 2,000 mg/kg (estimated)		
Skin Irritation:		May cause skin irrita	May cause skin irritation.		
Eye Irritation:		May cause eye irrita	May cause eye irritation.		
Sensitization:		Not a skin sensitizer	Not a skin sensitizer.		
Carcinogenicity:		Not classified as car	Not classified as carcinogenic.		
12. Ecological Inform	ation				
Ecotoxicity:		No data available.	No data available.		
Persistence and Degradability:		No data available.	No data available.		
Bioaccumulative Potential:		No data available.	No data available.		
	rations				
13. Disposal Conside		al, regional, national, and interna	tional regulations.		
13. Disposal Conside Dispose of waste material in ac	cordance with all loca	al, regional, national, and interna	tional regulations.		
13. Disposal ConsideDispose of waste material in ac14. Transport Information	cordance with all loca				
 13. Disposal Conside Dispose of waste material in ac 14. Transport Informa The data provided in this section 	cordance with all loca ation on is for information o	nly and may not be specific to yo	ur package size ormode of transport. You will need to		
 13. Disposal Conside Dispose of waste material in ac 14. Transport Informa The data provided in this section apply the appropriate regulation 	cordance with all loca ation on is for information o ns to properly classify	nly and may not be specific to yo y your shipment for transportatio	ur package size ormode of transport. You will need to n.		
 13. Disposal Conside Dispose of waste material in ac 14. Transport Informa The data provided in this section 	cordance with all loca ation on is for information o ns to properly classify UN	nly and may not be specific to yo	ur package size ormode of transport. You will need to		
 13. Disposal Conside Dispose of waste material in ac 14. Transport Informa The data provided in this section apply the appropriate regulation 	cordance with all loca ation on is for information o ns to properly classify	nly and may not be specific to yo y your shipment for transportatio	ur package size ormode of transport. You will need to n.		
 13. Disposal Consider Dispose of waste material in action 14. Transport Information The data provided in this section apply the appropriate regulation Regulatory information 	cordance with all loca ation on is for information o ns to properly classify UN number	nly and may not be specific to yo y your shipment for transportatio Proper shipping name RESIN / HARDENER RESIN / HARDENER	ur package size ormode of transport. You will need to n. Classes/Packing Group		
 13. Disposal Conside Dispose of waste material in ac 14. Transport Information The data provided in this section apply the appropriate regulation Regulatory information CFR 	cordance with all loca ation on is for information o ins to properly classify UN number 3082 / 2735	nly and may not be specific to yo y your shipment for transportatio Proper shipping name RESIN / HARDENER	ur package size ormode of transport. You will need to n. Classes/Packing Group Class 8 III		

15. Regulatory Information

There are no established exposure limits for the mixture, however, dust and fumes from processing should be ventilated adequately. To the best of our knowledge:

None of the mixture components are on the health & safety reporting list.

YES

None of the mixture components are in this product are under a Chemical Test Rule.

None of the mixture components are listed under TSCA section 12b (export notification).

None of the mixture components in this material have an SNUR under TSCA.

None of the mixture components in this material have an RQ under CERLCA.

None of the mixture components in this material have a TPQ under SARA.

None of the mixture components in this material is reported under section 313.

Clean Air Act:

Marine Polluted :

This material does not contain any hazardous air pollutants.

Clean Water Act: None of the chemicals in this product are listed as hazardous substances under the CWA.

None of the chemicals in this product are listed as priority pollutants under CWA.

None of the chemicals in this product are listed as toxic pollutants under CWA.

OSHA:



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02
 +92-309-7772464

left www.ressichem.com



None of the chemicals in this product are considered highly hazardous by OSHACalifornia Prop 65:California no significant risk level: none of the chemicals in this product are listed. European / International RegulationsEuropean labeling in accordance with EU/EC Directives.Hazard Symbols:not availableRisk Phrases:no Information availableSafety Phrases:no Information availableWGK:no Information available.

16. Other Information

This Material Safety Data Sheet (MSDS) is provided for informational purposes only. The information contained herein is believed to be accurate, but no representations, guarantees, or warranties of any kind are made to its accuracy, reliability, or completeness.



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
 +92-21-32593800-02 +92-309-7772464
 www.ressichem.com