



Zepoxy Pigment Paste is a series of standard easy-to-disperse epoxy compatible pigment pastes based on opaque pigments with excellent color fastness properties.

TECHNICAL DATA

Property	Test Method	Result
Appearance	Visual	Thick, flowable liquid
Recommended dosage	Theoretical	0.1 – 10% of resin
*Viscosity @ 25°C	ASTM D 2196-05	150,000 – 300,000 cPs

^{*}Typical results under laboratory conditions

PERFORMANCE CHARACTERISTICS

- Mixes easily.
- Can be mixed to develop custom colors.
- → High color fastness.
- High gloss.
- ✓ No flocculation as faced with powder pigments.
- Opaque finish.
- ✓ Non-Toxic.
- ✓ Low odor.

AVAILABLE COLORS

Red, Orange, Yellow, Green, Blue, Black, White

USAGE:

Add Pigment to Resin (Part A). If unsure of ratios, add pigment in very small amounts until the desired color is achieved. Add no more than 10% pigment by weight to resin. After thoroughly mixing pigment into resin, add the hardener. The pigmented resin can also be stored for later use.

PACKAGING

Zepoxy Pigment Paste is available as follows:

100ml, 1KG, 5KG and 20 KG

HEALTH AND SAFETY

Dispose containers of the materials as per local laws, rules, and regulations. Use gloves, safety masks and other safety apparel as per health and safety laws. For further assistance, please refer to the MSDS of the product for further health and safety information.



D-83, S.I.T.E., Industrial Area, Manghopir Road, Karachi - 75530, Pakistan
+92-21-32593800-02
+92-309-7772464