

Zepoxy REH 115 EC is high viscosity reactive polyamide curing agent to be used with Solvent-based Epoxy Resin in various coating applications.

APPLICATIONS

- ✓ Tank and pipe coating
- ✓ Masonry and pool coatings
- ✓ Maintenance and marine coating
- ✓ High gloss coatings

ADVANTAGES

- ✓ Blended with other amine-based hardeners.
- ✓ Excellent adhesion.
- ✓ Good toughness and flexibility.
- ✓ Good pigment and substrate wetting.
- ✓ Long pot life.

TECHNICAL DATA

Property	Test Method	Result
Appearance	Visual	Pale brown high viscous liquid
*Color	ASTM D 1544	9 max.
*Amine value	ASTM D 1652	200-240 Mg KOH/gm
*Viscosity @ 25°C	ASTM D 2196	200,000 - 700,000 cPs
AHEW	-	190
Mix ratio w/ RER 011X75	-	30 PHR
Flash Point	ASTM D 93	>102°C

*Typical results under laboratory conditions.

PACKAGING

Zepoxy REH 115EC is available as follows:

1 KG, 5KG, 15KG, 30KG, and 200KG

HEALTH AND SAFETY

Dispose containers of the materials as per local laws, rules, and regulations. Use gloves, safety masks and other safety apparel as per health and safety laws. For further assistance, please refer to the MSDS of the product for further health and safety information.