

Zepoxy REH 115 is high viscosity reactive polyamide curing agent with high imidazole content for Epoxy Resin to be used in various adhesive and coating applications.

APPLICATIONS

- ✓ Tank and pipe coating
- ✓ Masonry and pool coatings
- ✓ Maintenance and marine coating
- ✓ High gloss coatings
- ✓ Adhesives and grouts

ADVANTAGES

- ✓ Blended with other Amine-based hardeners.
- ✓ Excellent adhesion.
- ✓ Good toughness and flexibility.
- ✓ Good pigment and substrate wetting.
- ✓ Long pot life.

TECHNICAL DATA

Property	Test Method	Result
Appearance	Visual	Clear, yellow to brown highly viscous liquid
*Color	ASTM D 1544	9 max.
*Amine value	ASTM D 1652	270-300 mg KOH/g
*Viscosity @ 25°C	ASTM D 2196	200,000 - 700,000 cPs
*Equivalent weight approx.	-	190 AHEW
*Mixing ratio with RER 128	-	100 PHR
*Mixing ratio with RER 011X75	-	30 PHR

*Typical results under laboratory conditions.

PACKAGING

Zepoxy REH 115 is available as follows:

1 KG, 5KG, 15KG, 30KG, and 200KG

HEALTH AND SAFETY

Dispose containers of the materials as per local laws, rules, and regulations. Use gloves, safety masks and other safety apparel as per health and safety laws. For further assistance, please refer to the MSDS of the product for further health and safety information.